

#### SAFETY DATA SHEET

Section 1 - Identification

Product Identifier: Activator Part Number: ACT

Recommended Use: Activator to reduce cure temperature

of High Temperature coatings.

Manufacturer / Supplier:

Tech Line Coatings, Inc. 26844 ADAMS AVE. MURRIETA, CA 92562

USA

Phone 951-304-0834 Fax 951-461-9658

www.techlinecoatings.com

Restrictions on Use:

Keep out of reach of children.

Not recommended for use on Medical equipment. Not recommended for use on Aviation equipment.

Emergency Phone: (Chemtrec) 1-800-424-9300

#### Section 2 – Hazards Identification

Signal Word: Danger

Symbols:



#### Hazard Statements:

Highly flammable liquid and vapor

Toxic if swallowed

Toxic in contact with skin

Toxic if inhaled

Causes severe skin burns and eye damage

Causes serious eye damage

Suspected of causing cancer

Suspected of damaging fertility or the unborn child

Causes damage to organs; or May cause damage to organs;

liver, kidney, eyes, lungs, central nervous system

May be fatal if swallowed and enters airways

GHS Classification:	Category
Flammable Liquid	2
Acute Toxicity Oral	3
Acute Toxicity Dermal	3
Acute Toxicity Inhalation	3
Skin Corrosion	1
Eye Damage	1
Carcinogenicity	2
Toxic to Reproduction	2
Specific Target Organ Toxicity Single Exposure	1
Aspiration Hazard	1

#### **Precautionary Statements:**

Keep away from heat / sparks / open flames / hot surfaces. - No Smoking. Ground / bond container and receiving equipment. Use explosion proof electrical / ventilating / lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

In case of fire use alcohol-resistant foam, dry chemical or carbon dioxide

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Wear protective gloves / protective clothing (chemical proof). Wear eye protection and face protection. Wash hands, face and any exposed skin thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat drink or smoke when using this product. Do not breath fumes / mist / vapors / spray. Use only outdoors or in a well ventilated area.

If swallowed: immediately call a poison center / doctor for medical advice. Do NOT induce vomiting.

If on skin: wash with plenty of water. Call a poison center / doctor if you feel unwell or if irritation occurs. Immediately take off all contaminated clothing and wash it before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center / doctor for medical advice.

If in eyes: Rinse cautiously in water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor.

If exposed or concerned: Get medical advise / attention, from a poison center / doctor.

Dispose of Contents / container in accordance with regulations in your area. See section 13 for additional information.

Section 3 – Composition / Information On Ingredients

Component Name	Common Name / Synonyms	CAS#	% of Weight	
Ethanol	Ethyl Alcohol	64-17-5	> 42%	
Trade Secret		Trade Secret	> 45%	
Isopropanol	2-Propanol, Isopropyl Alcohol	67-63-0	2 to 5%	
Methanol	Methyl Alcohol	67-56-1	1 to 3%	
Methy Isobutyl Ketone	MIK, Isopropylacetone	108-10-1	0 to 0.5%	

Other ingredients are not hazardous based on OSHA standard Section 29 CFR 1910.1200

#### Section 4 – First Aid Measures

#### General Advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water, and remove contaminated clothing shoes and leather goods. Consult a physician..

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

# Note To Physician

Moderately toxic by swallowing. May cause acute kidney injury (renal cortical tubular necrosis) by massive peroral overdose or sustained skin contact. Due to the severely irritating or corrosive nature of the material, swallowing may lead to ulceration and inflammation of the upper alimentary tract with hemorrhage and fluid loss.

Also, perforation of the esophagus or stomach may occur, leading to mediastinitis or peritonitis and the resultant complications. This material reacts immediately with water in the acid contents of the stomach to produce ethanol. Although ethanol production may occur, and there is a potential for nephrotoxicity, because of its intensely irritating effects, it is unlikely that large volumes of this material will be acutely ingested. Therefore, the irritant and aspiration hazards from regurgitation are more serious causes for concern. In view of this, it is recommended that emesis should not be induced in the conscious patient, neither mechanically nor pharmacologically. If it is considered necessary to evacuate the stomach contents, this should be undertaken with caution in order to avoid perforation of inflamed or ulcerated areas of the upper alimentary tract, or to avoid aspiration (e.g., gastric lavage in the presence of endotracheal intubation).

<u>Section 5 – Fire Fighting Measures</u>

Extinguishing Media:	Special Fire Fighting Procedures:		
Use alcohol-resistant foam, dry chemical or carbon dioxide.	Wear self contained breathing apparatus for fire fighting if		
	necessary.		
Unusual Fire And Explosion Hazards:	Additional Information:		
Hazardous decomposition products formed under extreme	Use water spray to cool unopened containers.		
fire conditions Carbon and other oxides. Vapors are			
heavier than air and may travel to a source of ignition and			
flash back.			

# Section 6 – Accidental Release Measures

### Methods for Containment and Clean Up

- Soak up with inert absorbent material. Sand, silica gel, acid binder or universal binder.
- Keep in suitable, marked and closed containers for disposal.
- Use spark-proof tools and explosion-proof equipment.
- Remove sources of ignition.
- Warn other workers of spill.
- Wear personal protective equipment
  - NIOSH Approved Respirator
  - Gloves
  - Safety Glasses
- Do not allow material to be released into the environment.

# Additional Information:

- See Section 7 for safe handling information.
- See Section 8 for PPE information
- See Section 13 for disposal information

### Section 7 – Handling And Storage

#### Handling:

Do not breathe vapors or mists from spraying. Avoid contact with skin and eyes. Use with adequate ventilation to maintain exposure levels below established exposure limits. Wear personal protective equipment. If required wear an appropriate NIOSH approved respirator with paint prefilter. Use explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges. Protect from moisture.

# Storage:

Store in area suitable for flammable liquids. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Protect from oxidizers, inorganic acids, aldehydes, and isocyanates.

<u>Section 8 – Exposure Controls And Personal Protection</u>

Component	ACGIH TLV	OSHA PEL	NIOSH REL	
Ethanol	1000 ppm TWA	1000 ppm TWA	1000 ppm TWA	
Trade Secret	No data available	No data available	No data available	
Isopropanol	200 ppm TWA	400 ppm TWA	400 ppm TWA	
Methanol	200 ppm TWA	200 ppm TWA	200 ppm TWA	
Methy Isobutyl Ketone	50 ppm TWA	50 ppm TWA	50 ppm TWA	

**Engineering Controls:** Exhaust ventilation.

Showers

Eyewash stations

Use in a well-ventilated area.

**Respiratory Protection:** Use NIOSH approved respirator if TWA/TLV limits are exceeded

Protective Gloves: CHEMICAL RESISTANT

**Eye Protection:** SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES

Other Protective Equipment: WEAR PROTECTIVE CLOTHING, CHEMICAL RESISTANT OR OTHER PROTECTIVE

OUTERWEAR, AVOID CONTACT WITH SKIN OR EYES

**Ventilation:** Local Exhaust: Use To Maintain Below TWA Limits

Mechanical: Use Non-Sparking Equipment

Work / Hygienic Practices: wash thoroughly after handling product and before eating, drinking or smoking

#### Section 9 – Physical And Chemical Properties

Form: liquid
Color: Clear
Odor: Alcohol

Odor Threshold: Not Established
pH: No data available
Melting point/range: No data available

Initial boiling point :  $> 148^{\circ}$  F. Flash point :  $> 49^{\circ}$  F.

Evaporation Rate:

Upper/lower flammability or explosive limits:

No data available on mixture

Vapor pressure

No data available on mixture

Vapor density > 1 - (air =1) Relative density 941.5 g/l

Solubility(ies)

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

No data available on mixture

No data available on mixture

No data available on mixture

Total VOC < 940 g/l

# Section 10 - Stability And Reactivity

Stability: STABLE

**Possibility of hazardous reactions:** Hazardous Polymerization: Will not occur.

**Conditions to avoid:** Avoid storage of open containers at elevated temperatures. Heat, flames

and sparks, direct sunlight.

**Incompatible Materials:** Reaction with acid, water or other aqueous media is exothermic.

**Hazardous Decomposition Products:** Thermal breakdown of this product during fire or very high heat conditions

may evolve the following decomposition products: Silicon dioxide. Carbon

oxides. Metal oxides. Formaldehyde.

# Section 11 - Toxicological Information

**Potential Health Effects** 

**Inhalation** Toxic if inhaled.

**Ingestion** Toxic if swallowed. May be fatal if swallowed and enters airways

Skin Toxic in contact with skin. Causes severe skin burns damage

Eyes Causes severe eye damage

**Acute Toxicity** 

Ethanol Oral LD50 LD50 Oral - rat - 7,060 mg/kg

Remarks: Lungs, Thorax, or Respiration:Other changes.

Inhalation LC50 LC50 Inhalation - rat - 10 h - 20000 ppm

Dermal LD50 no data available

Trade Secret Oral LD50 LD50 Oral - rat - 3500 mg/kg

Inhalation LC50 No data available

Dermal LD50 LD50 Dermal - rabbit - 4000 mg/kg

LD50 Oral - rat - > 10000 mg/kgLD50 Oral - rat - 5,045 mg/kg

Isopropanol Oral LD50 Remarks: Behavioral:Altered sleep time (including change in righting reflex).

Behavioral:Somnolence (generaldepressed activity).

Inhalation LC50 LC50 Inhalation - rat - 8 h - 16000 ppm

Dermal LD50 LD50 Dermal - rabbit - 12,800 mg/kg

Methanol Oral LD50 LD50 Oral - rat - 13,000 mg/kgLDLO Oral - Human - 143 mg/kg

Remarks: Lungs, Thorax, or Respiration:Dyspnea. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

LD50 Oral - rat - 1,187 - 2,769 mg/kg

Inhalation LC50 LC50 Inhalation - rat - 4 h - 128.2 mg/l

LC50 Inhalation - rat - 6 h - 87.6 mg/l

Dermal LD50 LD50 Dermal - rabbit - 17,100 mg/kg

Methy Isobutyl Ketone Oral LD50

LD50 Oral - rat - 2,080 mg/kg

Inhalation LC50 LC50 Inhalation - rat - 4 h - 8.2 - 16.4 mg/m3

Dermal LD50 LD50 Dermal - rabbit - > 16,000 mg/kg

# Skin Corrosion/Irritation

Ethanol

Skin - rabbit - Irritating to skin. - 24 h

Trade Secret Corrosive to skin Isopropanol

Skin - rabbit - Mild skin irritation

Methy Isobutyl Ketone

Skin - rabbit - Mild skin irritation - 24 h

### Serious Eye Damage/Eye Irritation

Ethanol

Eyes - rabbit - Mild eye irritation - 24 h - Draize Test

Trade Secret

Eyes - rabbit - very markedly irritating

Isopropanol

Eyes - rabbit - Eye irritation - 24 h

Methy Isobutyl Ketone

Eyes - rabbit - Moderate eye irritation - 24 h

# Respiratory Or Skin Sensitization

No data available

# Germ Cell Mutagenicity

Methanol

Genotoxicity in vitro - Ames test - S. typhimurium - with and without metabolic activation - negative

Genotoxicity in vitro - in vitro assay - fibroblast - negative

Mutation in mammalian somatic cells

Genotoxicity in vivo - mouse - male and female - Intraperitoneal - negative

## Carcinogenicity

IARC: Isopropanol

3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol)

Methy Isobutyl Ketone

2B - Group 2B: Possibly carcinogenic to humans (4-Methylpentan-2-one)

Other: Ethanol

Carcinogenicity - mouse - Oral

Tumorigenic:Equivocal tumorigenic agent by RTECS criteria. Liver:Tumors. Blood:Lymphomas including

Hodgkin'svdisease

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or

potential carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or

potential carcinogen by OSHA.

This product contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

# **Reproductive Toxicity**

Ethanol

Reproductive toxicity - Human - female - Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects. Effects on

Newborn: Drug dependence.

Methanol

Fertility classification not possible from current data.

# Specific Target Organ Toxicity Single Exposure

Isopropanol

May cause drowsiness or dizziness.

Methanol

Causes damage to organs.

Methy Isobutyl Ketone

May cause respiratory irritation.

### Specific Target Organ Toxicity Repeated Or Prolonged Exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

## **Aspiration Hazard**

Aspiration into the lungs can cause fatal chemical pneumonitis.

# Section 12 - Ecological Information

## General Comments:

Do not allow material to be released into the environment without proper governmental permits

# **Environmental Toxicity:**

Ethanol

Toxicity to fish No data available

Toxicity to daphnia and other aquatic No data available

invertebrates

Toxicity to algae No Data Available

Trade Secret

Toxicity to fish LC50 Species: Brachydanio rerio Result: > 934 mg/l Exposure time: 96 h Method:

OECD Test Guideline 203

Toxicity to daphnia and other aquatic

invertebrates

EC50 Species: Daphnia magna Result: 331 mg/l Exposure time: 48 h Method:

OECD-Guideline 202

Toxicity to algae EC50 Species: Desmodesmus subspicatus (green algae) Result: > 1,000 mg/l

Exposure time: 72 h

NOEC Species: Desmodesmus subspicatus (green algae) Result: 1.3 mg/l Exposure

time: 72 h

Toxicity to microorganisms EC10 Species: Pseudomonas putida Result: 13 mg/l Exposure time: 5.75 h

EC50 Species: Pseudomonas putida Result: 43 mg/l Exposure time: 5.75 h

Isopropanol

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 9,640.00 mg/l - 96 h

Toxicity to daphnia and other aquatic EC50 - Daphnia magna (Water flea) - 5,102.00 mg/l - 24 h

invertebrates Immobilization EC50 - Daphnia magna (Water flea) - 6,851 mg/l - 24 h

Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - > 2,000.00 mg/l - 72 h

EC50 - Algae - > 1,000.00 mg/l - 24 h

Methanol

Toxicity to fish mortality LC50 - Lepomis macrochirus (Bluegill) - 15,400.0 mg/l - 96 h

NOEC - Oryzias latipes - 7,900 mg/l - 200 h

Toxicity to daphnia and other aquatic

invertebrates

EC50 - Daphnia magna (Water flea) - > 10,000.00 mg/l - 48 h

Toxicity to algae Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) -

22,000.0 mg/l -96 h

Methy Isobutyl Ketone

Toxicity to fish LCO - Leuciscus idus melanotus - 480 mg/l - 48 h

Toxicity to daphnia and other aquatic

invertebrates

EC50 - Daphnia magna (Water flea) - 1,550 - 3,623 mg/l - 24 h

Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - 980 - 2,000 mg/l - 48 h

Environmental Toxicity on mixture: No data available

## Section 13 – Disposal Considerations

### Waste Disposal Method:

#### RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? Yes

Characteristic Waste:

Ignitable: D001 TCLP: D018

State or local laws may impose additional regulatory requirements regarding disposal.

# **Contaminated Packaging**

Dispose of as unused product.

### <u>Section 14 – Transportation Information</u>

**Hazardous for Shipping:** Yes

Based on 49 CFR, IATA and IMDG:

UN Number: UN3469

**UN Proper Shipping Name:** Paint, flammable, corrosive

Hazard Class: 3 (8)
Packing Group:

Labels: Flammable Liquid, Corrosive

Placards: Flammable Liquid, Corrosive

# Section 15 – Regulations

TSCA (Toxic Substances Control Act) Regulations, 40 CFR 710: All hazardous ingredients are on the TSCA Chemical Substance Inventory.

Component	%	CAS Number	SARA 313	SARA 302	New Jersey RTK List	Pennsylvania RTK List	Massachusetts RTK List	California Prop 65 list
Ethanol	> 42%	64-17-5	no	no	Yes	Yes	Yes	No
Trade Secret	> 45%	Trade Secret	Yes	No	TBD	TBD	TBD	No
Isopropanol	2 to 5%	67-63-0	Yes	No	Yes	Yes	Yes	No
Methanol	1 to 3%	67-56-1	Yes	No	Yes	Yes	Yes	No
Methy Isobutyl Ketone	0 to 0.5%	108-10-1	Yes	No	Yes	Yes	Yes	Yes

TBD: To Be Determined by examining sections 2 and 11 of this SDS as the listing requirments of the Right to Know (RTK) legislation varies from state to state.

SARA 311 / 312 Hazards: Flammable Hazard ,Acute Health Hazard, Chronic Health Hazard

### Section 16 - Other Information

**Date Prepared:** 10/02/2013

Date Updated:

**Date Printed:** 10/02/2013

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Tech Line Coatings, Inc., knowledge or obtained from sources believed by Tech Line Coatings, Inc. to be accurate but does not purport to be all inclusive, and Tech Line Coatings, Inc., does not assume any legal responsibility for use or reliance upon same. Before using any chemical, read its label, instructions and material safety data sheet.